

Tower Pro

Tower Pro is a high-voltage product designed for residential energy storage applications. It supports a maximum of 12 clusters in parallel and provides an energy capacity range from 7.68 kWh to 276.48 kWh. The system allows for a maximum 1C charge and discharge, and its stackable auto-configuration modules simplify installation and maintenance.



Flexible Expansion

Up to 12 clusters in parallel,
7.68kWh--276.48kWh capacity



Ultra Safe

Intelligent fire extinguishing system,
detects and extinguishes fire in 5s



Battery Equalization

Free mixing of modules
within three years



Automatic Self-heating

-20°C to 55°C operating
temperature








Easy Installation

0 wiring, installation in 15 minutes by
one person, save time and labor



1C Charge/Discharge

Simultaneously supplying power
to multiple loads, no need to
worry about power outages

Model	Tower Pro TP7	Tower Pro TP11	Tower Pro TP15	Tower Pro TP19	Tower Pro TP23
Product Pattern					
Battery Module Type	LiFePO ₄	LiFePO ₄	LiFePO ₄	LiFePO ₄	LiFePO ₄
Battery Module Quantity	2	3	4	5	6
Rated Energy	7.68 kWh	11.52 kWh	15.36 kWh	19.2 kWh	23.04 kWh
Usable Energy	7.296 kWh	10.944 kWh	14.592 kWh	18.24 kWh	21.888 kWh
Operating Voltage	168~216V	252~324V	336~432V	420~540V	504~648V
Nominal Voltage	192V	288V	384V	480V	576V
Nominal Capacity	40Ah	40Ah	40Ah	40Ah	40Ah
Max. Continuous Charge/Discharge Power*	7.68 kW	11.52 kW	15.36 kW	19.2 kW	23.04 kW
Recommended Depth of Discharge (DOD)	95%	95%	95%	95%	95%
Dimensions [W/D/H] (mm)	587/310/788	587/310/1009	587/310/1230	587/310/1451	587/310/1672
Net Weight [kg]	109.5	150	190.5	231	271.5
Charging Temperature Range	0~55°C/-20~55°C (with heating function)				
Discharging Temperature Range	-10~55°C/-20~55°C (with heating function)				
Communication	CAN/RS485/RS232				
Cycle life**	≥8000 Cycles				
Protection Level	IP55				
Warranty	10 Year				
Heating Function	PI Heating (Optional)				
Fire Protection Function	Aerosol fire extinguishing				
OTA Remote Upgrade Function	Equipped				
Battery Module Name	HV9640				
Expansion	Max. 12 Tower Pro can be connected in parallel				
Certification	IEC62619/IEC63056/IEC62477/IEC62040/CE-EMC/VDE2510-50				
Compatible Inverters	kostal/Ingeteam/Solis/GoodWe/Growatt/Solplanet/SAJ/DEYE/Hoymiles/SOLINTEG/Kaco ect.				

* Maximum Continuous Discharge/Charge Power when communicating with inverter is 1C

** Test conditions:0.2C Charging&Discharging.@25°C,95%DOD

